

JHC-060A

J SERIES AC CROSSFLOW FAN



VOLTAGE	120V~230V
BEARINGS	Ball Bearings
MOTOR	AC Capacitor Type 1ø 2p
IMPELLER	Aluminum Alloy
LENGTH (C)	Min 15.9in (405mm), Max 31.7in (805mm)
AIRFLOW	120~268 CFM (3.4~7.6m³/min)
OPERATING TEMP	0°C~45°C
OPERATING LIFE	30,000 hours @ 40°C

Model Number	inches (mm)			V	Hz	A	W	RPM	Pressure (P)		Airflow (Q)		dBA	kg
	A	B	C						mmAq	inH ₂ O	m³/min	CFM		
JHC-06030A1223-3B	12.0 (306)	12.6 (321)	15.9 (405)	120	60	0.31	34	3100	2.5	0.10	4.0	141	52	1.80
				220	50/60	0.17/0.18	29/34	2650/3000	1.8/2.4	0.07/0.09	3.4/3.8	120/134	48/51	
				230	50	0.17	32	2650	1.8	0.07	3.4	120	48	
JHC-06036A1223-3B	14.4 (366)	15.0 (381)	18.3 (465)	120	60	0.33	36	3000	2.5	0.10	4.8	170	51	1.85
				220	50/60	0.17/0.19	31/37	2550/2850	1.9/2.2	0.07/0.08	4.2/4.6	148/162	47/50	
				230	50	0.18	33	2600	1.9	0.07	4.2	148	48	
JHC-06042A1223-3B	16.8 (426)	17.4 (441)	20.7 (525)	120	60	0.35	39	2850	2.3	0.09	5.5	194	51	1.90
				220	50/60	0.18/0.20	33/39	2500/2700	1.9/2.2	0.07/0.08	4.9/5.2	173/184	47/49	
				230	50	0.18	35	2500	1.9	0.07	4.9	173	47	
JHC-06052A1223-3B	20.1 (526)	21.3 (541)	24.6 (625)	120	60	0.37	42	2700	2.0	0.08	6.7	237	50	2.05
				220	50/60	0.19/0.21	35/42	2400/2550	1.8/1.8	0.07/0.07	5.9/6.2	208/219	46/47	
				230	50	0.19	37	2450	1.8	0.07	6.0	212	47	
JHC-06060A1223-3B	23.9 (606)	24.4 (621)	27.8 (705)	120	60	0.38	43	2600	1.9	0.07	7.3	258	49	2.15
				220	50/60	0.19/0.22	36/42	2300/2400	1.8/1.9	0.07	6.5/6.7	230/237	46/47	
				230	50	0.19	38	2350	1.9	0.07	6.6	233	47	
JHC-06070A1223-3B	27.8 (706)	28.4 (721)	31.7 (805)	120	60	0.39	44	2400	1.7	0.07	7.6	268	47	2.25
				220	50/60	0.20/0.22	38/43	2150/2200	1.6/1.7	0.06/0.07	6.8/7.0	240/247	44/44	
				230	50	0.20	40	2200	1.7	0.07	7.0	247	45	

