

JED-040A/JE3-040A/JF3-040A

J SERIES DC CROSSFLOW FAN



SINGLE BLOWER

VOLTAGE	12V, 24V
BEARINGS	Ball Bearings
MOTOR	DC Brushless Type/3-phase
IMPELLER	Aluminum Alloy
LENGTH (C)	Min 5.2in (133mm), Max 34.3in (870mm)
AIRFLOW	25~162 CFM (0.7~4.6m³/min)
OPERATING TEMP	0°C~45°C
OPERATING LIFE	30,000 hours @ 40°C

Model Number		inches (mm)				V	A	RPM	Pressure (P)		Airflow (Q)		dBA	g	Blower
		A	B	C	D				mmAq	inH ₂ O	m³/min	CFM			
JED-04009A12-3B	①	3.9	4.3	5.2	1.2	12	0.22	2950	2.5	0.098	0.7	25	37	220	Single
JED-04009A24-3B	①	(98)	(108)	(133)	(31)	24	0.17								
JED-04015A12-3B	②	6.3	6.7	7.7	1.2	12	0.28	2500	1.9	0.074	1.0	35	37	260	Single
JED-04015A24-3B	②	(160)	(170)	(195)	(31)	24	0.19								
JE3-04019A12-3B	③	7.8	8.2	9.2	1.2	12	0.29	2400	2.2	0.087	1.3	46	36	275	Single
JE3-04019A24-3B	③	(198)	(208)	(233)	(31)	24	0.16								
JE3-04029A12-3B	④	11.8	12.2	13.2	1.2	12	0.33	2000	1.6	0.063	1.8	64	32	350	Single
JE3-04029A24-3B	④	(300)	(310)	(335)	(31)	24	0.18								
JE3-04030A24-3B	⑤	12.2	12.6	13.8	1.5	24	0.30	2600	3.0	0.012	2.7	95	39	420	Single
JE3-04035A24-3B	⑥	14.2	14.6	15.7	1.5	24	0.32	2450	2.6	0.102	3.0	106	38	470	Single
JE3-04040A24-3B	⑦	16.1	16.5	17.7	1.5	24	0.34	2300	2.5	0.098	3.5	124	37	510	Single
JF3-04030X2A24-3B	⑧	24.8	25.2	26.4	1.5	24	0.26	1800	1.4	0.055	3.7	131	39	690	Double
JF3-04035X2A24-3B	⑨	28.7	29.1	30.3	1.5	24	0.27	1750	1.4	0.055	4.2	148	38	770	Double
JF3-04040X2A24-3B	⑩	34.3	33.1	34.3	1.5	24	0.28	1600	1.3	0.051	4.6	162	37	830	Double

