EVERLINE®
UAV PROPULSION MOTORS
EV2800 SERIES

EV2812-1100

PROPELLER PERFORMANCE TEST

6 × 3.5 × 3 | 6S

PTI PELONIS TECHNOLOGIES

DIMENSIONAL DRAWING

All dimensions in millimeters



GENERAL SPECIFICATIONS

MOTOR

Stator Size:	2812
KV Rating:	1100 KV
Configuration:	12N14P
Dimensions:	33.4 × 40 mm
Weight:	78.9 g
Shaft Diameter:	5 mm
Lead-Wire Length:	250 mm
Wire Gauge:	18 AWG (1 mm²)

ELECTRICAL

Test Battery Configuration:	6S LiPo
Maximum Rated Speed:	29,100 RPM
Maximum Tested Speed:	23,229 RPM
Idle Current (20 V):	1.4 A
Peak Current:	55 A
Winding Resistance:	53.4 mΩ

PROPELLER PERFORMANCE DATA

PROPELLER: 6 × 3.5 × 3 | BATTERY: 6S LiPo

Throttle (%)	Voltage (V)	Current (A)	Speed (RPM)	Thrust (g)	Input Power (W)	Efficiency (g/W)
10	25.22	0.17	2,486	8	4.3	1.87
20	25.20	0.58	5,229	71	14.6	4.86
30	25.17	1.32	7,800	180	33.2	5.42
40	25.10	2.63	10,286	330	66.0	5.00
50	24.99	4.47	12,686	518	111.7	4.64
60	24.83	7.24	14,829	733	179.8	4.08
70	24.60	10.71	17,143	984	263.5	3.73
80	24.35	15.22	19,200	1,240	370.6	3.35
90	24.05	20.40	21,171	1,515	490.6	3.09
100	23.80	27.53	23,229	1,848	655.2	2.82

NORMALIZED TEST PERFORMANCE CURVES



CURVE INTERPRETATION

Curves are normalized representations of measured test data for visual comparison. Refer to the performance table for actual measured values.

ENGINEERING NOTES

Performance data is based on the bench-test conditions.

Actual performance may vary with installation, airflow, battery condition, ESC setup, and propeller variation.

Validate final selections using application-specific testing.

CONTACT

Product and application assistance:

SALES@PELONISTECH.COM

PELONISTECHNOLOGIES.COM