EVERLINE®
UAV PROPULSION MOTORS
EV2800 SERIES

EV2812-1100

PROPELLER PERFORMANCE TEST

6 × 3 × 3 | 4S

PTI PELONIS TECHNOLOGIES

DIMENSIONAL DRAWING

All dimensions in millimeters



GENERAL SPECIFICATIONS

MOTOR

Stator Size:	2812
KV Rating:	1100 KV
Configuration:	12N14P
Dimensions:	33.4 × 40 mm
Weight:	78.9 g
Shaft Diameter:	5 mm
Lead-Wire Length:	250 mm
Wire Gauge:	18 AWG (1 mm²)

ELECTRICAL

Test Battery Configuration:	4S LiPo
Maximum Rated Speed:	29,100 RPM
Maximum Tested Speed:	17,229 RPM
Idle Current (20 V):	1.4 A
Peak Current:	55 A
Winding Resistance:	53.4 mΩ

PROPELLER PERFORMANCE DATA

PROPELLER: 6 × 3 × 3 | BATTERY: 4S LiPo

Throttle (%)	Voltage (V)	Current (A)	Speed (RPM)	Thrust (g)	Input Power (W)	Efficiency (g/W)
10	16.80	0.15	1,629	2	2.5	0.79
20	16.78	0.34	3,514	16	5.7	2.80
30	16.76	0.65	5,314	49	10.9	4.50
40	16.72	1.18	7,200	100	19.7	5.07
50	16.67	1.82	8,914	164	30.3	5.41
60	16.60	2.81	10,629	244	46.6	5.32
70	16.51	4.00	12,257	330	66.0	5.00
80	16.39	5.52	13,800	432	90.5	4.77
90	16.25	7.38	15,429	550	119.9	4.59
100	16.07	10.29	17,229	690	165.4	4.17

NORMALIZED TEST PERFORMANCE CURVES



CURVE INTERPRETATION

Curves are normalized representations of measured test data for visual comparison. Refer to the performance table for actual measured values.

ENGINEERING NOTES

Performance data is based on the bench-test conditions.

Actual performance may vary with installation, airflow, battery condition, ESC setup, and propeller variation.

Validate final selections using application-specific testing.

CONTACT

Product and application assistance:

SALES@PELONISTECH.COM

PELONISTECHNOLOGIES.COM