EVERLINE®
UAV PROPULSION MOTORS
EV3100 SERIES

EV3115-900


PROPELLER PERFORMANCE TEST

9 × 4 × 3 | 6S

PTI PELONIS TECHNOLOGIES

DIMENSIONAL DRAWING

All dimensions in millimeters



GENERAL SPECIFICATIONS

MOTOR

Stator Size:	3115
KV Rating:	900 KV
Configuration:	12N14P
Dimensions:	37 × 47 mm
Weight:	120 g
Shaft Diameter:	5 mm
Lead-Wire Length:	300 mm
Wire Gauge:	16 AWG (1.5 mm²)

ELECTRICAL


Test Battery Configuration:	6S LiPo
Maximum Rated Speed:	24,500 RPM
Maximum Tested Speed:	17,743 RPM
Idle Current (20 V):	2 A
Peak Current:	45 A
Winding Resistance:	38 mΩ

PROPELLER PERFORMANCE DATA

PROPELLER: 9 × 4 × 3 | BATTERY: 6S LiPo

Throttle (%)	Voltage (V)	Current (A)	Speed (RPM)	Thrust (g)	Input Power (W)	Efficiency (g/W)
10	25.22	0.21	2,057	32	5.3	6.04
20	25.20	0.83	4,276	144	20.9	6.88
30	25.13	2.10	6,343	346	52.8	6.56
40	25.01	4.33	8,314	652	108.3	6.02
50	24.81	8.12	10,200	1,022	201.5	5.07
60	24.48	13.20	11,914	1,456	323.1	4.51
70	24.14	19.89	13,457	1,926	480.1	4.01
80	23.73	26.95	14,914	2,369	639.5	3.70
90	23.26	36.60	16,200	2,845	851.3	3.34
100	22.90	49.11	17,743	3,423	1,124.6	3.04

NORMALIZED TEST PERFORMANCE CURVES



CURVE INTERPRETATION

Curves are normalized representations of measured test data for visual comparison. Refer to the performance table for actual measured values.

ENGINEERING NOTES

Performance data is based on the bench-test conditions.

Actual performance may vary with installation, airflow, battery condition, ESC setup, and propeller variation.

Validate final selections using application-specific testing.

CONTACT

Product and application assistance:

SALES@PELONISTECH.COM

PELONISTECHNOLOGIES.COM