

DIMENSIONAL DRAWING

All dimensions in millimeters

GENERAL SPECIFICATIONS

MOTOR

Stator Size:

4215

KV Rating:

380 KV

Configuration:

12N14P

Dimensions:

49 × 65 mm

Weight:

175 g

Shaft Diameter:

6 mm

Lead-Wire Length:

750 mm

Wire Gauge:

14 AWG (2.5 mm²)

ELECTRICAL

Test Battery Configuration:

6S LiPo

Maximum Rated Speed:

12,340 RPM

Maximum Tested Speed:

8,571 RPM

Idle Current (20 V):

1.4 A


Peak Current:

51 A

Winding Resistance:

66 mΩ

PROPELLER PERFORMANCE DATA						
PROPELLER: 10 × 5 × 3 BATTERY: 6S LiPo						
Throttle (%)	Voltage (V)	Current (A)	Speed (RPM)	Thrust (g)	Input Power (W)	Efficiency (g/W)
10	25.22	0.12	686	13	3.0	4.30
20	25.22	0.28	1,714	47	7.1	6.66
30	25.20	0.60	2,486	114	15.1	7.54
40	25.19	1.15	3,429	222	29.0	7.66
50	25.15	1.71	4,286	334	43.0	7.77
60	25.10	2.75	5,057	480	69.0	6.95
70	25.01	3.78	5,914	641	94.5	6.78
80	24.94	5.49	6,771	843	136.9	6.16
90	24.80	7.36	7,629	1,085	182.5	5.94
100	24.64	10.09	8,571	1,385	248.6	5.57



CURVE INTERPRETATION

Curves are normalized representations of measured test data for visual comparison. Refer to the performance table for actual measured values.

ENGINEERING NOTES

Performance data is based on the bench-test conditions.

Actual performance may vary with installation, airflow, battery condition, ESC setup, and propeller variation.

Validate final selections using application-specific testing.

CONTACT

Product and application assistance:

SALES@PELONISTECH.COM

PELONISTECHNOLOGIES.COM